

# Summertime Your Port-A-Cool®

*By performing the following simple steps, a Port-A-Cool® unit will continue to produce effective cooling throughout the summer.*



- 1) Inspect cooling media for break down, such as sagging or gapping. Clean if dirty. Replace if needed.
- 2) Check the fan blade to make sure it rotates freely.
- 3) Make sure the fan belt is tight and in good condition.
- 4) Oil the motor if necessary.
- 5) Check and clean Inline Strainer.
- 6) Clean Sump Tank and Spray Bar.
- 7) Pump should be clear of any obstructions
- 8) Make sure Drain Valve is closed and spray Bar Adjustment Valve is open (approximately 3 turns).
- 9) Determine if water and power source are adequate.
- 10) Fill reservoir before turning pump "on."
- 11) Make sure Float Valve operates properly.

*Refer to Port-A-Cool® Owner's Manual for specific maintenance instructions and troubleshooting guide.*

**DO YOU HAVE QUESTIONS OR NEED TO PLACE A PARTS ORDER?**

Call your Port-A-Cool® Distributor or Port-A-Cool® Technical Support at 888-COOL-AID (888-266-5243)



Port-A-Cool® units are manufactured by  
Port-A-Cool, L.L.C. • Center, TX  
[www.port-a-cool.com](http://www.port-a-cool.com)